



技术规范:

额定电流 : 3AMP

适用温度 : -40°C to +105°C

接触电阻 : 20mΩ Max

绝缘电阻 : 1000MΩ Min

耐电压 : AC 1000V



绝缘材料 : Polyester (UL94V-0)

Standard: PBT

端子材质 : Brass

电镀规范 : Au or Sn Over 50u" Ni

Pin#	尺寸A	尺寸B	尺寸C
2x5	10.16	21.68	31.90
2x6	12.70	24.22	34.44
2x7	15.24	26.76	36.98
2x8	17.78	29.30	39.52
2x9	20.32	31.84	42.06
2x10	22.86	34.38	44.60
2x11	25.40	36.92	47.14
2x12	27.94	39.46	49.68
2x13	30.48	42.00	52.22
2x14	33.02	44.54	54.76
2x15	35.56	47.08	57.30
2x16	38.10	49.62	59.84
2x17	40.64	52.16	62.38
2x18	43.18	54.70	64.92
2x19	45.72	57.24	67.46
2x20	48.26	59.78	70.00
2x21	50.80	62.32	72.54
2x22	53.34	64.86	75.08
2x23	55.88	67.40	77.62
2x24	58.42	69.94	80.16
2x25	60.96	72.48	82.70
2x26	63.50	75.02	85.24
2x27	66.04	77.56	87.78
2x28	68.58	80.10	90.32
2x29	71.12	82.64	92.86
2x30	73.66	85.18	95.40
2x31	76.20	87.72	97.94
2x32	78.74	90.26	100.48
2x33	81.28	92.80	103.02
2x34	83.82	95.34	105.56
2x35	86.36	97.88	108.10
2x36	88.90	100.42	110.64
2x37	91.44	102.96	113.18
2x38	93.98	105.50	115.72
2x39	96.52	108.04	118.26
2x40	99.06	110.58	120.80



插接系列	间距	型式	双排	单排	Pin数	电接	规格	角度	端子	备注
c-0.8mm			1-单排	1-单排	1"9P/50P	A-11"	A-706	S-80°	22.5mm间距25	0-3.0
b-1.0mm			2-双排	2-双排	2"40/50P	B-51"	B-706	R-90°	11.0mm间距18	1-3.0/0.6 (双排)
c-1.27mm			3-三排	3-三排	3"40/50P	C-50"	C-706	R-90°	12.2mm间距22	2-3.0/3.0 (双排)
d-2.0mm			4-四排	4-四排	4"40/50P	D-100"	D-706	L-90°	14.5mm间距26	3-2.8/4.0 (双排)
e-2.54mm					5"40/50P	E-150"	E-706	L-135°	17.5mm间距30	4-2.8/4.5 (双排)
f-3.50mm						F-200"			20.0mm间距36	其它另做说明
h-5.08mm						H-250"			25.0mm间距45	

注: 长脚材料另议

上海狮拓电子科技有限公司



TOLERANCE:

X	±0.05
XX	±0.10
ANG.	

產品名稱:
產品料號:

THIRD ANGLE PROJECTION



姓名: _____ 日期: _____

日期: _____

客户确认

日期: _____

日期: _____

2.54mm间距牛角, 90°, 立高13.0mm
Spec: 2.54mm Female Header, Dual Row, Right Angle
Positions: 2x5, 2x40
Plastics Height: 13.0mm