

P. C. B LAYOUT

Technical Data


Material:  
 Pin(outer sleeve):Brass,machined CuZn38Pb2  
 Plating(outer sleeve):  
 Tin Plated:2µm/80µm"NI, 5µm/200µ"Sn  
 Gold Plated:2µm"/80µm"Ni, 0.8µ" gold  
 Plating(Contact ):2µm/80µ"NI, gold or Tin plated  
 Insulator:PPS UL94V-0  
 ClIp(Contact 3 Flnger):Beryllium copper,heat teated  
 Mating pin□:0.38mm/0.50mm

Electrlcal:

Current rating:1Amps/contact max.  
 Contact resistance:Max 20mΩ  
 Dlelectric strength:Min 500V RMS  
 Operaling voltage:60VAC/DC

Mechanical:

-Insertion:0.5N typ  
 -Withdrawal:0.2N typ  
 Mechanical lige:min 500 cycle  
 Operaling temperature:-40° C to+105° C  
 Soldering temperature:+255° C



TOLERANCE:
X. ±XXX
.X ±0.20
.XX ±0.10
ANG.

	<h1>上海狮拓电子科技有限公司</h1>	
	產品名稱: 產品料號:	THIRD ANGLE PROJECTION

簽名 _____	客戶確認 <input type="checkbox"/> 承認 _____ 日期 _____ <input type="checkbox"/> 駁回 _____ 日期 _____
日期 _____	
審核 _____	
日期 _____	

STOA1-DXXXXXX0640B