



Technical Data

Material:

Pin(outer sleeve): Brass, machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated: $2\mu\text{m}/80\mu\text{m}''\text{Ni}$, $5\mu\text{m}/200\mu\text{m}''\text{Sn}$

Gold Plated: $2\mu\text{m}''/80\mu\text{m}''\text{Ni}$, $0.8\mu\text{m}''$ gold

Insulator: PPS UL94V-0

Mating pin \square : $0.47/0.50\text{mm}$

Electrical:

Current rating: 3Amps/contact max.

Contact resistance: $\leq 4\text{m}\Omega/\text{contact}$

Insulation resistance: $\geq 1000\text{M}\Omega$ at $V=100\text{V}$

Operating voltage: 60VAC/DC

Mechanical:

Mechanical life: min 500 cycle

Operating temperature: -40°C to $+105^\circ\text{C}$

Soldering temperature: $+255^\circ\text{C}$

P. C. B LAYOUT

TOLERANCE:

X. $\pm XXX$

.X ± 0.20

.XX ± 0.10

ANG.



上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION

簽名
日期
審核
日期

客戶確認

承認 _____ 日期 _____
 駁回 _____ 日期 _____

STOC1-DXXXX1000A-2